

### SECTION 1: IDENTIFICATION

#### Product Identifier

**Product Form:** Mixture

**Product Name:** Waterproofing with PTEF

**Product Code:** 15003700, 15003718

#### Intended Use of the Product

Waterproofing

#### Name, Address, and Telephone of the Responsible Party

##### Company

West Marine

500 Westridge Drive

Watsonville, CA 95076

(831) 728-2700

[www.westmarine.com](http://www.westmarine.com)

#### Emergency Telephone Number

**Emergency Number** : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### GHS-US/CA Classification

Flam. Liq. 4 H227

STOT RE 1 H372

Asp. Tox. 1 H304

Full text of hazard classes and H-statements : see section 16

#### Label Elements

##### GHS-US/CA Labeling

**Hazard Pictograms (GHS-US/CA)** :



GHS08

**Signal Word (GHS-US/CA)** :

Danger

**Hazard Statements (GHS-US/CA)** :

H227 - Combustible liquid.

H304 - May be fatal if swallowed and enters airways.

H372 - Causes damage to organs (central nervous system) through prolonged or repeated exposure.

**Precautionary Statements (GHS-US/CA)** :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P314 - Get medical advice/attention if you feel unwell.

P331 - Do NOT induce vomiting.

P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.

P403 - Store in a well-ventilated place.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

# Waterproofing with PTEF

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### Other Hazards

Aquatic Acute 2 H401

Aquatic Chronic 3 H412

H401 - Toxic to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

P273 - Avoid release to the environment.

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Petroleum distillates, hydrotreated light**	(CAS No) 64742-47-8	80 – 100	Flam. Liq. 4, H227 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Solvent naphtha, petroleum, medium aliphatic**	(CAS No) 64742-88-7	1 - 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Polytetrafluoroethylene	(CAS No) 9002-84-0	0.0375	Comb. Dust

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

\*\* The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES

### Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** May be fatal if swallowed and enters airways. Causes damage to organs (central nervous system) through prolonged or repeated exposure.

**Inhalation:** Prolonged exposure may cause irritation. Headache. Central nervous system effects.

**Skin Contact:** Prolonged exposure may cause skin irritation.

**Eye Contact:** May cause slight irritation to eyes.

**Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** Causes damage to organs (central nervous system) through prolonged or repeated exposure.

### Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

# Waterproofing with PTEF

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

## SECTION 5: FIRE FIGHTING MEASURES

### Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid. Will float and can be reignited on water surface.

### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Combustible liquid.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Remove containers from fire area if this can be done without risk. Do not breathe fumes or vapors from fire. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Thermal decomposition generates: Carbon oxides (CO, CO<sub>2</sub>). Hydrocarbons. Nitrogen oxides. Silicon oxides. Acrid smoke and irritating fumes.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

### Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

#### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Eliminate ignition sources. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Ventilate area. Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, and spray. Take precautionary measures against static discharge. Use only non-sparking tools. Use appropriate personal protective equipment (PPE).

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

# Waterproofing with PTEF

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

## Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep container tightly closed. Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep in fireproof place. Store locked up/ in a secure area.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

## Specific End Use(s)

Waterproofing

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Polytetrafluoroethylene (9002-84-0)		
Québec	VEMP (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup> (decomposition products)
Petroleum distillates, hydrotreated light (64742-47-8)		
British Columbia	OEL TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures)

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

**Hand Protection:** Wear protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**Environmental Exposure Controls:** Avoid release to the environment.

**Other Information:** When using, do not eat, drink or smoke

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear to amber liquid
Odor	: Petroleum
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: - 70 °C (-94 °F)
Freezing Point	: Not available
Boiling Point	: 149 - 204.5 °C (300.2 - 400.1 °F)
Flash Point	: 62.5 °C (144.5 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available

# Waterproofing with PTEF

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: 0.78 at 20 °C (68 °F)
Solubility	: Insoluble in water.
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

**Chemical Stability:** Combustible liquid. May form flammable or explosive vapor-air mixture.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Inhalation:vapor: Not classified.

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

**Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs (central nervous system) through prolonged or repeated exposure.

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation. Headache. Central nervous system effects.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** Causes damage to organs (central nervous system) through prolonged or repeated exposure.

### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
LD50 Oral Rat	> 25 ml/kg
LD50 Dermal Rabbit	> 3000 mg/kg
LC50 Inhalation Rat	> 13 mg/l/4h
Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l/4h

# Waterproofing with PTEF

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Polytetrafluoroethylene (9002-84-0)</b>	
<b>IARC Group</b>	3
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
<b>National Toxicology Program (NTP) Status</b>	Evidence of Carcinogenicity.

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

**Ecology - General:** Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
<b>LC50 Fish 1</b>	800 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>EC50 Daphnia 1</b>	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
<b>LC50 Fish 1</b>	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>LC50 Fish 2</b>	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

### Persistence and Degradability

<b>Waterproofing with PTEF</b>	
<b>Persistence and Degradability</b>	May cause long-term adverse effects in the environment.

### Bioaccumulative Potential

<b>Waterproofing with PTEF</b>	
<b>Bioaccumulative Potential</b>	Not established.
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
<b>BCF Fish 1</b>	(bioaccumulation expected)
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
<b>BCF Fish 1</b>	61 - 159

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### In Accordance with DOT

**Proper Shipping Name** : COMBUSTIBLE LIQUID, N.O.S. (Petroleum distillates)  
**Identification Number** : NA1993  
**Packing Group** : III  
**ERG Number** : 128  
**Marine Pollutant** : No  
**Additional Information** : This product meets the limited quantity exceptions as follows: DOT: Not regulated as dangerous goods except when shipped in bulk. Otherwise, the above descriptions apply.

**In Accordance with IMDG** Not regulated for transport

**In Accordance with IATA** Not regulated for transport

**In Accordance with TDG** Not regulated for transport

# Waterproofing with PTEF

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

<b>Waterproofing with PTEF</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Fire hazard Health hazard - Aspiration hazard Health hazard - Specific target organ toxicity (single or repeated exposure)
<b>Polytetrafluoroethylene (9002-84-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C))
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### US State Regulations

<b>Polytetrafluoroethylene (9002-84-0)</b>	
RTK - U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	

### Canadian Regulations

<b>Polytetrafluoroethylene (9002-84-0)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

<b>Revision Date</b>	: 06/15/2018
<b>Other Information</b>	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR).

### GHS Full Text Phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Comb. Dust	Combustible Dust
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2


# Waterproofing with PTEF

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

- NFPA Health Hazard** : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA Fire Hazard** : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
- NFPA Reactivity Hazard** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US, Mex)