

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Vinyl Cleaner

Product Code: 15003742

Intended Use of the Product

Use of the Substance/Mixture: Cleaner

Name, Address, and Telephone of the Responsible Party

Company

West Marine

500 Westridge Drive

Watsonville, CA 95076

www.westmarine.com

Phone Number: (831) 728-2700

Emergency Telephone Number

Emergency number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Carc. 2 H351

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



GHS07



GHS08

Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) : H315 - Causes skin irritation

H319 - Causes serious eye irritation

H351 - Suspected of causing cancer

Precautionary Statements (GHS-US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P264 - Wash hands, forearms and exposed areas thoroughly after handling.

P280 - Wear eye protection, protective gloves, protective clothing.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P321 - Specific treatment (see Section 4).

P332+P337+P313 - If skin irritation occurs or eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P405+P501 - Store locked up. Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Aquatic Acute 3

H402 - Harmful to aquatic life

P273 - Avoid release to the environment

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Vinyl Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Tetrasodium EDTA	(CAS No) 64-02-8	1 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Dam. 1, H318 Aquatic Acute 2, H401
Alcohols, C9-11, ethoxylated	(CAS No) 68439-46-3	1 - 5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
Diethylene glycol monobutyl ether	(CAS No) 112-34-5	1 - 5	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
Nitrilotriacetic acid trisodium salt	(CAS No) 5064-31-3	0.1 - 1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319 Carc. 2, H351
Sodium hydroxide	(CAS No) 1310-73-2	0.1 - 1	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Obtain medical attention if pain, blinking or redness persist.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Irritating to eyes, respiratory system and skin.

Inhalation: May cause respiratory irritation.

Skin Contact: Causes skin irritation.

Eye Contact: Causes serious eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Suspected of causing cancer.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use carbon dioxide. Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: May be corrosive to metals over a prolonged period of contact.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Toxic fumes are released.

Vinyl Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reference to Other Sections Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not allow contact with metals. Do not get in eyes, on skin, or on clothing. Do NOT breathe (vapor, mist, gas).

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and contain spill with inert material, then place in suitable container.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Storage areas should be periodically checked for integrity.

Incompatible Materials: Strong acids. Strong oxidizers. Metals.

Special Rules on Packaging: Store in original container.

Specific End Use(s) Cleaner.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Diethylene glycol monobutyl ether (112-34-5)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
Manitoba	OEL TWA (ppm)	10 ppm
Newfoundland & Labrador	OEL TWA (ppm)	10 ppm
Nova Scotia	OEL TWA (ppm)	10 ppm
Prince Edward Island	OEL TWA (ppm)	10 ppm
Sodium hydroxide (1310-73-2)		
Mexico	OEL Ceiling (mg/m ³)	2 mg/m ³
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	10 mg/m ³
Alberta	OEL Ceiling (mg/m ³)	2 mg/m ³
British Columbia	OEL Ceiling (mg/m ³)	2 mg/m ³
Manitoba	OEL Ceiling (mg/m ³)	2 mg/m ³
New Brunswick	OEL Ceiling (mg/m ³)	2 mg/m ³
Newfoundland & Labrador	OEL Ceiling (mg/m ³)	2 mg/m ³
Nova Scotia	OEL Ceiling (mg/m ³)	2 mg/m ³
Nunavut	OEL Ceiling (mg/m ³)	2 mg/m ³
Northwest Territories	OEL Ceiling (mg/m ³)	2 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Prince Edward Island	OEL Ceiling (mg/m ³)	2 mg/m ³

Vinyl Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Québec	PLAFOND (mg/m ³)	2 mg/m ³
Saskatchewan	OEL Ceiling (mg/m ³)	2 mg/m ³
Yukon	OEL Ceiling (mg/m ³)	2 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Protective clothing. Safety glasses. Face shield. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Corrosionproof clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear
Odor	: Pleasant
Odor Threshold	: Not available
pH	: 12
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting/Freezing Point	: 0 °C (32 °F)
Boiling Point	: Not available
Flash Point	: > 100 °C (> 212 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Upper/Lower Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density/Specific Gravity	: 1.003 (water = 1)
Solubility	: Water: High
Partition coefficient: n-octanol/water	: Not available
Viscosity	: 6.5 cSt @ 100 °C (212 °F)
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: May be corrosive to metals over a prolonged period of contact.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Contact with metallic substances.

Incompatible Materials: Oxidizers. Strong acids. Alkalis and caustic products. Halogens. Metals.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Thermal decomposition generates toxic vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

Vinyl Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes serious eye irritation. (pH: 12; alkali reserve: 2.52)

Serious Eye Damage/Irritation: Causes skin irritation. (pH: 12; alkali reserve: 2.52)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Suspected of causing cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Causes skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Alcohols, C9-11, ethoxylated (68439-46-3)	
LD50 Oral Rat	1400 mg/kg
Tetrasodium EDTA (64-02-8)	
LD50 Oral Rat	1780 mg/kg
Diethylene glycol monobutyl ether (112-34-5)	
LD50 Oral Rat	3384 mg/kg
LD50 Dermal Rabbit	2700 mg/kg
Nitrilotriacetic acid trisodium salt (5064-31-3)	
LD50 Oral Rat	920 mg/kg
LC50 Inhalation Rat (mg/l)	> 5 mg/l/4h
Nitrilotriacetic acid trisodium salt (5064-31-3)	
IARC Group	2B

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life.

Tetrasodium EDTA (64-02-8)	
LC50 Fish 1	41 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Other Aquatic Organisms 1	1.01 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
LC 50 Fish 2	59.8 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Sodium hydroxide (1310-73-2)	
LC50 Fish 1	40 mg/l
Nitrilotriacetic acid trisodium salt (5064-31-3)	
LC50 Fish 1	93 - 170 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	560 - 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	175 - 225 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Diethylene glycol monobutyl ether (112-34-5)	
LC50 Fish 1	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	> 100 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
Persistence and Degradability	
Vinyl Cleaner	
Persistence and Degradability	Not established.

Vinyl Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Bioaccumulative Potential

Vinyl Cleaner	
Bioaccumulative Potential	Not established.
Diethylene glycol monobutyl ether (112-34-5)	
BCF fish 1	(no bioconcentration expected)

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

UN Number Not regulated for transport

UN Proper Shipping Name Not regulated for transport

Additional Information Not available

Transport by sea Not regulated for transport

Air transport Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Vinyl Cleaner	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
Alcohols, C9-11, ethoxylated (68439-46-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Nitrilotriacetic acid trisodium salt (5064-31-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Sodium hydroxide (1310-73-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Tetrasodium EDTA (64-02-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Diethylene glycol monobutyl ether (112-34-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

US State Regulations

Alcohols, C9-11, ethoxylated (68439-46-3)	
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Nitrilotriacetic acid trisodium salt (5064-31-3)	
U.S. - Illinois - Toxic Air Contaminant Carcinogens U.S. - Illinois - Toxic Air Contaminants U.S. - Massachusetts - Right To Know List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Tetrasodium EDTA (64-02-8)	
U.S. - Texas - Effects Screening Levels - Long Term	

Vinyl Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Texas - Effects Screening Levels - Short Term

Sodium hydroxide (1310-73-2)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - Ceilings
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - Ceilings
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - Ceilings
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - Ceilings
U.S. - Washington - Permissible Exposure Limits - Ceilings
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Diethylene glycol monobutyl ether (112-34-5)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations


Vinyl Cleaner

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Vinyl Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Alcohols, C9-11, ethoxylated (68439-46-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Tetrasodium EDTA (64-02-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Nitrilotriacetic acid trisodium salt (5064-31-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Class E - Corrosive Material

Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification Class E - Corrosive Material

Diethylene glycol monobutyl ether (112-34-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class B Division 3 - Combustible Liquid
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATA ON DATE OF PREPARATION OR LAST REVISION

Revision date : 06/23/2014

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:


Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H351	Suspected of causing cancer
H401	Toxic to aquatic life
H402	Harmful to aquatic life

Vinyl Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- NFPA Health Hazard** : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- NFPA Fire Hazard** : 0 - Materials that will not burn.
- NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Party Responsible for the Preparation of This Document

West Marine

Phone Number: (831) 728-2700

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS